

Digital Trust Services – Qualified Trust Services

How to Initialize SafeNet 5110cc

1. Double click on the **"Safenet Authentication Client Tools"** icon at the right side of your computer screen



2. Select **"Advanced View"** by pressing on the gear icon as shown in the picture below.

SafeNet Authentication Client Tools		- 🗆 X
		gemalto*
SafeNet Auther	ntication	Client 🛛 🎯 👩 🛔 🤋 🎰
		Advanced View
Card #19A1209FB7633DA3	1	Rename Token
	****	Change Token Password
	1	Unlock Token
	\odot	Delete Token Content
	2	View Token Info
		Disconnect SafeNet Virtual Token
		→ GEMALTO.COM

3. Press on the "Initialize" icon as shown in the picture below.

SafeNet Authentication Client Tools		- · · ×
SafeNet Authe	ntication Clier	nt 🛛 🐲 😳 🧯 🤋 🎰
SafeNet Authentication Client Tools	To Initialize Token Token Category Reader name Serial number (PKCS#11) Free space (minimum estimated) Hardware version Card ID (GUID) Product name Card type Applet Version Mask version Color Supported key size Token Password	Image Image Card #19A1209FB7633DA3 Hardware AKS ifdh 0 19A1209FB7633DA3 1981209FB7633DA3 15834 16.0 16.1 0x6C00002A4CB13C746C00002A4CB13C74 SafeNet =Token 5110 CC ID Prime Java Applet 4.0.2.K G280/Fk17 N/A 2048 bits Present Present
	Token Password retries remaining Maximum Token Password retries Token Password expiration	No expiration
		⊖ GEMALTO.COM

4. Choose "Preserve the token settings and policies" and click Next.

Initialize Token	- Initialization Options	×		
SafeNet Aut	hentication Client	gemalto		
	Waming! This operation will delete all token content.			
	Please choose the way you want to initialize the token:			
	• Preserve the token settings and policies			
	Configure all initialization settings and policies			
				SafeNet Authentication Client Tools
				If the current password is the strongly recommended to upd to keep your token secure.
	< Back Next > Finish	Cancel	1	

5. Tick the boxes "Use factory default administrator password" and "Use factory default digital signature PUK" and click Next

*(In case your have the old firmware there might be only one box, just tick that)

Use factory default adn	tor Password to initialize the Token - ninistrator password	
Administrator Password:	•••••••••	
<u> </u>	nature PUK to initialize the Token —	
Use factory default digi	tal signature PUK	
Digital Signature PUK:	•••••	
		Current Language: EN
The default administrator o	assword and digital signature PUK is	a known value of 0's set on th

6. Set your New Token Password and confirm it, untick the box of "**Token password must be changed on first logon**" and tick on the "**Keep the current administrator password**" click OK on the pop-up window and then click **Next**

≶ Initialize Token -	Password Settings		×
SafeNet Auth	entication Client	t	gemalto
Token Name:	MPKI-Prod		
Create Token Pas	sword		
New Token Pass	word:	•••••	
Confirm Password	i:	•••••	
Create Administrato Create Administra		•••••	
Confirm Password	ł:	•••••	•••••
Keep the cum	ent administrator password		
			Current Language: EN

7. Set you New Digital Signature PIN and confirm it, and on the "New Digital Signature PUK" and the "Confirm PUK" set 6 times zero (000000) and click Finish.

S Initialize Token - IDPrime Common	n Criteria Settings X
SafeNet Authentication	Client genalto [×]
Common Criteria Passwords:	
New Digital Signature PIN:	•••••
Confirm PIN:	• • • • • • • •
	PIN Policy
New Digital Signature PUK:	•••••
Confirm PUK:	•••••
	PIN Policy
< E	Back Next > Finish Cancel

8. On the Initialize Token Notification click **OK**



9. Finally, after the Initialization of the Token is completed click **OK** again.